Part No.: 165315 Vendor Part No.: S21-LED-F001841

Synergy 21 LED Flex Strip 60 NW DC24V 24W IP65 CRI>90 sideview





kwh/1000h:	26,40
Lumens:	2350
Watt:	24,0
Nominal Service Life:	35000 Std.
Switching Cycles:	50000
Opt. Ambient Temperature.:	25 °C



Synergy 21 LED Flex Strip

Length: 5m Voltage: 24V, Watt: 4,8W/m, 24W

Light colour: nw, 4500K, CRI>90 Brightness: 470lm/m, total: 2350lm

Beam angle: 120° Protection class: IP65

Number of LEDs: 60 SMD/m, total: 300LEDs

Dimensions: 5000*8*3 mm

PCB colour: white, open cable end red black (350±5mm)

Working temperature: -25°C to +50°C Can be shortened every 6 LEDs 10cm Adhesive tape: yes 3M on the back

Energy efficiency class: A+

kWh/1000h: 26.4

Strip can be shortened at the cut marks with sharp scissors. !Attention! Strip must first be checked for functionality. Only split the strip when no current is present.

Our 3M adhesive tape adheres well, but should only be used as a mounting aid.

There are a variety of mounting options, such as clips, permanently elastic mounting adhesive, cable ties, etc.



Part No.: 165315 Vendor Part No.: S21-LED-F001841

Please note that LED strips must also be cooled.

Make sure that the LED strip does not exceed a working temperature of 40°C, otherwise its service life cannot be guaranteed.

No guarantee can be given for overheated LED strips.

Attributes

Attribute	Value
Abstrahlwinkel:	120
Ampere:	1
CC oder CV:	CV
CRI:	>90
Dimmbar:	abhängig vom Netzteil
LED Strip Klebeband:	ja
LED Strip Breite:	8
LED Strip Höhe:	3
LED Strip Klebeband:	ja
LED Strip kürzbar:	100
LED Strip Länge:	5000
Lichtfabe in Kelvin:	4500
Lichtfarbe:	neutralweiß
Lichtfarbe in Kelvin:	4500
Lichtfarbe Name:	neutralweiß
Lumen:	2350
Schutzklasse:	IP65
Volt:	24
Weight:	0.35 Kg
Warranty:	60.00 Months


Additional Images

SYNERGY 21

Part No.: 165315 Vendor Part No.: S21-LED-F001841







Accessories

Part No.	Name
93682	Mean Well Power Supply - 24V 150W Dimmable IP65