

NOTE:

- 1. Panel frame:PC plastic surface treatment with transparent window
- 2. Mounting plate nickel plating T=1.5mm
- 3. Panel bracket SPCC T=1.5mm with plastic powder cladding frosting surface treatment

4. Accessory:

- 1. Cable Tie(75X1.9mm) *24pcs
- 2. Screw and Nut M6*18mm × 4set



5. RoHS 2011/65/EU and amendment directives (EU)

2015/863 compliant;REACH 1907/2006/EC compliant.

6. Packing:1pcs/PE bag+Inner box 10pcs/outcarton

ITEM NO.	Body Colour	Logo Colour
S216336V3	Gray RAL 7035	SYNERGY 2 ® pantone black C / 1 pantone blue 298C
S216337V3	Black RAL 9005	SYNERGY 2 ® white / 1 pantone blue 298C

						SYNERGY 21					
						CUSTOMER			ITEM NO.		
		Add black	2024-01-09	A2	PRODUCT NAME	19" 1U 24 ports blank Patch panel Three-piece type shielded	MANUFACTURE COUNTRY:	CHINA	UNIT	MM	
		Change the mold type	2023-03-06	A1	DRAWNBY	CHECKBY	APPOBY	DATE			
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.	SYNERGY 21	SYNERGY 21	SYNERGY 21	2023-1-04			



NOTES:

ELECTRICAL:

- 1.Contact Resistance : 20MΩ MAX
- 2. Insulation Resistance : 500MΩ MIN @ 500V DC
- 3. Withstand Voltage : DC 1000V AC 700V RMS 60Hz, 1MIN
- 4. Compliance with Class EA up to 500 MHz to ISO/IEC 11801 Ed. 2. 2:2011-06
DIN EN 50173-1:2011-09

ENVIRONMENTAL:

- 1.Storage temperature : -40℃ T0+70℃
- 2. Operation temperature : -10℃ to+60℃

MECHANICAL

- 1. SHIELD MATERIAL: ZINC ALLOY
 - 2. IDC MATERIAL: PC TERMINAL:PHOSPHOR BRONZE, TIN PLATING
 - 3.RJ45 Contact Life: 750 Times Min
 - 4. Plug inforce:<30N
 - 5. Solid cable:1/22AWG(0.65MM)-1/26AWG(0.40MM) ID:1.05MM-1.5MM
 - 6. Cable OD: 5.0mm-8.5mm
 - 7. PoE per IEEE 802.3af,PoE+ per IEEE 802.3at
 - 8. 360° Shield connection
- RoHS 2011/65/EU and amendment directives (EU)
2015/863 compliant;REACH 1907/2006/EC compliant.
PACKING:lpc+copper foil/PE bag+label
Accessories:
Instruction Sheet *lpc/inner box
Cable Tie(75X1.9mm) *1Pc

MATERIAL LIST:

⑧	Dust cap	PC Black	1	
⑦	MODULAR COVER	PC White	1	
⑥	RJ 45 JACK INSERT	PHOSPHOR BRONZE 8P8C GOLD PLATED	8	
⑤	PCB	1.2mm UL 94V0	1	
④	IDC BODY	PC White	1	
③	IDC PIN	PHOSPHOR BRONZE & TINNED	8	
②	LABEL COLOR CODE	T568A/B	2	
①	IDC TERMINAL	FOR 22-26AWG(0.40mm-0.65mm) CABLE	1	

NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
		NEW	2024-04-16	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

SYNERGY 21					
CUSTOMER	AN		ITEM NO.	S216338V2	
PRODUCT NAME	CAT. 6A STP KEYSTONE JACK	manufacture country:	china	UNIT	MM
DRAWNBY	CHECKBY	APPOBY	DATE		
SYNERGY 21	SYNERGY 21	SYNERGY 21	2024-04-16		