

ALLNET USB 3.0 Typ-A Network Adapter 2x + 1x USB 3.0 Hub ALL-NC-2G-102-USB-A "ALLTRAVEL"

>>> [Go to the shop article](#)



EAN CODE



ALLNET ALL-USB-to-LAN-102 USB 3.0 to Dual Port Gigabit Ethernet Adapter NIC w/ USB Port

- Add two Gigabit Ethernet ports and a USB 3.0 pass-through port to your laptop through a single USB 3.0 port

The USB 3.0 to Dual Port Gigabit Ethernet Adapter lets you add two Gigabit Ethernet ports to your laptop or Ultrabook™ computer through a single USB 3.0 port, and features an integrated USB 3.0 pass-through port that keeps your USB port available for use with external storage or other peripherals. Each RJ45 port supports 10/100/1000 Mbps Ethernet and is fully compatible with IEEE 802.3i/u/ab standards.

This 2-port USB LAN adapter is a versatile solution for connecting to two separate physical networks simultaneously, leveraging the 5 Gbps speed of USB 3.0 to provide dedicated gigabit bandwidth to each port. The dual USB NIC is also ideal for providing dedicated physical network interfaces to virtual machine configurations. Great for IT administrators that require dual-homed or multi-homed host systems.

The USB 3.0 NIC supports IPv4/IPv6 packet Checksum Offload Engine (COE) and TCP large send offload to reduce the load on your CPU, as well as Jumbo Frames, full-duplex operation with 802.3x flow control, and VLAN tagging for an efficient and full-featured USB network adapter.

Applications

- Business or IT professionals that need to connect to two separate networks simultaneously
- Run a virtual machine(s) on a workstation, with access to separate physical network connections
- Replacement for a failed built-in Gigabit Ethernet port on a laptop

Feature



- Dual Gigabit Ethernet ports through a single USB connection
- Integrated USB 3.0 pass-through port
- IEEE 802.3, 802.3u and 802.3ab (10BASE-T, 100BASE-TX, and 1000BASE-T) compatible
- Crossover Detection & Auto-Correction (Auto MDIX)
- IEEE 802.1Q VLAN Tagging support
- Up to 4K Jumbo Frame support
- Supports Checksum Offload (IPv4, IPv6, TCP, UDP) and Large Send Offload
- Compact, lightweight design for maximum portability

Technical Details:

Information	
Hardware	
Bus Type	USB 3.0
Chipset ID	ASIX - AX88179 (2) VIA - VL811
Industry Standards	IEEE802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az
Interface	RJ45 (Gigabit Ethernet)
Ports	2
Performance	
Auto MDIX	Yes
Compatible Networks	10/100/1000 Mbps
Full Duplex Support	Yes
Jumbo Frame Support	4K max.
Max Distance	100 m / 330 ft
Maximum Data Transfer Rate	5 Gbps (USB 3.0) 2 Gbps (Ethernet - Full-Duplex)
Type and Rate	USB 3.0 - 5 Gbit/s
Connector(s)	
Connector Type(s)	1 - USB Type-A (9 pin) USB 3.0 Female
	1 - USB Type-A (9 pin) USB 3.0 Male
	2 - RJ-45 Female
Software	
OS Compatibility	Windows® XP, Vista, 7, 8, 8.1, 10 Windows Server® 2003, 2008 R2, 2012, 2012 R2, 2016 Mac OS® 10.6 to 10.12 - <i>VLAN tagging is currently not supported in Mac OS</i> Linux Kernel 2.6.25 to 4.11.x <i>LTS Versions only</i>
Special Notes / Requirements	



System and Cable Requirements		Available USB port
Indicators		
LED Indicators	1 - Gigabit Link/Activity (Amber)	
	2 - 10/100 Link/Activity (Green)	
Power		
Power Source	USB-Powered	
Environmental		
Humidity	5~85% RH	
Operating Temperature	0°C to 50°C (32°F to 122°F)	
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	
Physical Characteristics		
Cable Length		
Color	Black	
Enclosure Type	Plastic	
Form Factor	Attached Cable	
Product Height		
Product Length		
Product Weight		
Product Width		
Packaging Information		
Shipping (Package) Weight		
What's in the Box		
Included in Package	1 - USB 3.0 Dual Network Adapter	
	1 - Driver CD	
	1 - Instruction Manual	