
# Cyber Power

# **REPLACEMENT BATTERY PACK SERIES**



# REPLACEABLE BATTERY PACK TO REVIVE UPS PERFORMANCE

RBP0016

## Easily replaceable battery pack to bring your UPS back to life

Designed for Uninterruptible Power Supply (UPS), the Replacement Battery Pack (RBP) Series restores life to UPS systems to maintain the system's performance. The ready-to-use battery packs allow users to replace batteries easily. The RBPs adopt leak-proof sealed lead-acid batteries which are stable and safe, to ensure the power system's reliability. The batteries are certified by CyberPower, guaranteeing the products' high quality and safety.

#### COMPATIBLE UPS

• PFC Sinewave Series

### SERIES FEATURES

- Sealed Lead-acid Batteries
- Guaranteed Compatibility

- Longer Battery Life
- Maintenance-free

Leak-proof Design

## **TECHNICAL SPECIFICATIONS**

| Model Name  | RBP0016                         |  |
|---|---------------------------------|--|
| General   |                                 |  |
| Nominal Output Voltage (Vdc)                        | 24                              |  |
| Battery   |                                 |  |
| Battery Type  | Sealed Lead-acid                |  |
| Battery Quantity (pcs)                              | 2                               |  |
| Physical Size                                       |                                 |  |
| Dimensions (WxHxD) (in.)                            | 7.9 x 2.6 x 5.9                 |  |
| Dimensions (WxHxD) (mm.)                            | 201.5 x 65 x 151                |  |
| Weight (lbs.)                                       | 13.2                            |  |
| Weight (kg.)  | 4.7                             |  |
| Shipping Dimensions                                 |                                 |  |
| Dimensions (WxHxD) (in.)                            | 9.8 x 3.7 x 12                  |  |
| Dimensions (WxHxD) (mm.)                            | 250 x 93 x 305                  |  |
| Weight (lbs.)                                       | 10.4                            |  |
| Weight (kg.)  | 6                               |  |
| Environmental                                       |                                 |  |
| Operating Temperature (°F)                          | 32 ~ 104                        |  |
| Operating Temperature (°C)                          | 0 - 40                          |  |
| Operating Relative Humidity<br>(Non-condensing) (%) | 0 - 95                          |  |
| Operating Elevation (feet/meters)                   | 0-9,843 feet (0-3,000 meters)   |  |
| Storage Temperature (°F)                            | 5 - 113                         |  |
| Storage Temperature (°C)                            | -15 ~ 45                        |  |
| Storage Relative Humidity<br>(Non-condensing) (%)   | 0 - 95                          |  |
| Storage Elevation (feet/meters)                     | 0-49,213 feet (0-15,000 meters) |  |

#All specifications are subject to change without notice

CyberPower and the CyberPower logo are trademarks of Cyber Power Systems, Inc., and/or affiliates, which are registered in many countries and regions. All other trademarks are the property of their respective owners.