

ALLNET Switch industrial full managed Layer2+ 6 Port GbE • PoE Budget 120W • 4x PoE at • 2x SFP • Fanless • DIN • JSON • ALL-SGI8106PMJ

>>> Vers l'article de la boutique en ligne



EAN CODE



ALLNET Switch industrial full managed Layer2+ 6 Port GbE • PoE Budget 120W • 4x PoE+ • 2x SFP • Fanless • DIN • JSON • ALL-SGI8106PMJ


Highlights:

- 4 Gigabit ports with PoE AF-AT support up to 30 watts per port
- 2x SFP ports for fibre optic GBIC e.g. ALL4750/4751-INDU etc.
- PoE ports 1-4 max. PoE IEEE802.3at 30W
- Layer2+ features such as 802.1Q VLAN, port isolation IGMP, LLDP, PoE+ management, IP source guard, ACLs etc.
- Supports spanning tree STP (802.1D) and RSTP (802.1W) and MSTP (802.1s)
- Supports PoE management such as PoE scheduling, PoE PD-alive, port PoE priority, soft reboot PoE non-stop
- Supports G.8032 quick ring protocol. Self-healing <20ms
- Max. PoE budget = 120 watts
- Freeless metal housing with optimised heat dissipation
- Easy to use as a table-top device, wall-mounted or top-hat rail
- Extended temperature range from -40°C ~ +75°C

ALLNET ALL-SGI8106PMJ L2+ managed switch with 4 ports PoE is an industrial switch with 4-port Gigabit 802.3af/at PoE + 2-port Gigabit SFP optical port. It has a robust IP40 housing and a redundant power supply system. The industrial managed switch offers user-friendly but advanced IPv6/IPv4 management interfaces and a soft reboot PoE non-stop function and is the best investment for expanding industrial companies or upgrading their network infrastructure.



Intelligent PD alive check for frozen PDs

The ALL-SGI8106PMJ industrial PoE switch with 8 ports can be configured to monitor the status of the connected PDs in real time. As soon as the PD stops working and responding, the ALL-SGI8106PMJ restarts the power supply to the PoE port and gets the PD up and running again. In addition, reliability is significantly improved by the fact that the PoE port resets the PD power supply, reducing the administrative burden on the administrator.



PoE schedule function for energy saving

To protect the environment, the ALL-SGI8106PMJ Ethernet PoE switch can effectively control the power supply in addition to its ability to deliver high wattage. The PoE schedule function helps to enable or disable the PoE power supply for each PoE port during specific time intervals and is a powerful feature that helps SMEs or enterprises to save power and money.



1000 BASE-T UTP With PoE

Planned PD restart


The intelligent PoE switch ALL-SGI8106PMJ allows each of the connected PoE IP cameras or PoE wireless access points to be restarted at a specific time every week. This reduces the risk of the IP camera or AP crashing due to a buffer overflow.



Redundant ring with fast recovery for critical network applications


The ALL-SGI8106PMJ supports redundant ring technology and has a strong, fast self-recovery capability to prevent interruptions and external intrusions. It integrates advanced ITU-T G.8032 ERPS technology, Spanning Tree Protocol (802.1s MSTP) and a redundant power supply system into the customer's industrial automation network to improve system reliability and uptime in harsh factory environments. In a given simple ring network, the data link recovery time can be as low as 20 ms.

ERPS Ring for Video Transmission Redundancy



1588 time protocol for industrial computer networks

The ALL-SGI8106PMJ is ideal for telecommunications and carrier Ethernet applications and supports MEF service provisioning and timing-over-packet solutions for IEEE 1588 and synchronous Ethernet.



Strong Layer 2 functions

The ALL-SGI8106PMJ Layer 2 Ethernet switch can be programmed for advanced Layer 2 switch management functions such as dynamic port link aggregation, 802.1Q tagged VLAN, Q-in-Q VLAN, private VLAN, Multiple Spanning Tree Protocol (MSTP), QoS, bandwidth control, IGMP snooping and MLD snooping. By aggregating the supporting ports, the ALL-SGI8106PMJ enables the operation of a high-speed trunk group that has multiple ports and also supports fail-over.

Efficient and versatile management methods

For efficient management, the ALL-SGI8106PMJ is equipped with console, web and SNMP management interfaces.

With the integrated web-based management interface, it offers a user-friendly, platform-independent management and configuration option.

For text-based management, access is possible via Telnet and the console port.

For standards-based monitoring and management software, it provides an SNMPv3 connection that encrypts the packet contents for secure remote management during each session.

Intelligent PoE switch with SFP DDM function

The ALL-SGI8106PMJ supports the SFP DDM (Digital Diagnostic Monitor) function, which allows the network administrator to easily monitor real-time parameters of the SFP transceivers, such as optical output power, optical input power, temperature, laser bias voltage and transceiver supply voltage.

The technical features and stable housing make the switch the ideal solution for industrial applications. Supplied



without power supply unit - please order separately!

Technical details:

Model	ALL-SGI8106PMJ
Copper Ports	4-10/100/1000BASE-T RJ45 auto-sensing ports
Fibre ports	2-100/1000BASE-T SFP interfaces, supports 100/1000Mbps dual mode
PoE ports	4-802.3af/802.3at PoE injector ports
Console ports	1 x RS-232-to-RJ45 serial port (115200, 8, N, 1)
Switch architecture	Store-and-Forward
Switch Fabric	12Gbps/non-blocking
Throughput	8.928Mpps @64 bytes
Address Table	8K entries
Share Data Buffer	4.1 Mb
Jumbo Frame	9216 bytes
SDRAM	1Gb
Flash memory	128Mb
Flow Control	IEEE 802.3x pause frame for full-duplex ; Back pressure for half-duplex
Reset button	>2 sec: Factory default and reset
Power Supply	48 ~ 57 VDC, 50/60Hz, Dual DC for PoE support 12VDC ~ 48VDC for non PoE support
PoE standards	IEEE 802.3af Power over Ethernet/PSE IEEE 802.3at Power over Ethernet Plus/PSE
PoE Power Supply Type	Per port 52V DC, 300mA. Max. 15.4 watts (IEEE 802.3af) Per port 52V DC, 600mA. Max. 30 watts (IEEE 802.3at)
LED indicators	Power: Green Solid on–power work normal, off–power disconnected System: Green Blink–work normally, solid on–soft work abnormal, fast blink–soft upgrade PoE: Yellow Solid on–PoE work normally, Off–PoE doesn't



	<p>work, Blink–PoE overload</p> <p>10/100/1000T RJ45 interfaces (Port 1 to Port 4): 1000 LNK/ACT (Green),</p> <p>Blink–port connected with data transmission;</p> <p>Solid on–port connected without data transmission</p> <p>100/1000Mbps SFP Interfaces (Port 5 to Port 6): Green</p> <p>Blink- port connected with data transmission;</p> <p>Solid on- port connected without data transmission</p>
EMC	<p>Surge Immunity:6KV Per: IEC61000-4-5</p> <p>ESD Protection: ESD Level 4 Per: IEC61000-4-2;EFT Level 4 Per: IEC61000-4-4</p>
Dimension	145x112x47.2mm
Weight	0.6kg
Working Temperature	-40°C to 75°C
Storage Temperature	-40°C to 80°C
Operation Humidity	5% to 95%, non-condensing
MTBF	50,000hrs

Layer 2 functions

Port configuration	<p>Auto-negotiation</p> <p>Flow control</p> <p>Port Mirror: TX/RX/BOTH; Many-to-1 monitor</p> <p>CPU Mirror</p> <p>Traffic statistics</p>
Link aggregation	<p>Static link aggregation</p> <p>LACP(Dynamic Trunk/Static Trunk)</p> <p>Algorithm based on Source/Destination MAC</p> <p>Algorithm based on Source/Destination IP</p>
MAC Table	Aging Time



	Static MAC address Dynamic MAC address management
VLAN	4094 Active VLANs 4094 VID 802.1Q Tag VLAN Port VLAN Protocol VLAN MAC VLAN Voice VLAN 802.1ad Q-in-Q tunnelling Private VLAN (Protected port) GARP/GVRP
ACL	256ACLs L2, L3 e L4 Time-based ACL IP ACL MAC ACL MAC-IP ACL User-Defined ACL ICMPv6
Spanning tree	802.1D Spanning Tree Protocol (STP) 802.1w Rapid Spanning Tree Protocol (RSTP) 802.1s Multiple Spanning Tree Protocol (MSTP) Loop Guard Root Guard TC-BPDU Guard



	<p>BPDU Guard</p> <p>BPDU Filter</p>
Ring Protection	<p><20ms G.8032 ERPS Ring</p> <p>Fast Ring</p> <p>ALLNET ring, < 20ms</p>
Multicast	<p>256 groups</p> <p>IGMP v1/v2/v3 Snooping, Fast Leave</p> <p>MLD Snooping</p> <p>Multicast VLAN</p> <p>IGMP filter</p> <p>MVR</p> <p>Multicast routing</p>
QOS	<p>8 mapping IDs to 8 level priority queues</p> <p>CoS port-based</p> <p>CoS 802.1p-based</p> <p>CoS DSCP-based</p> <p>Scheduling algorithms SP, WRR, SP+WRR</p> <p>Storm Control (Broadcast, Multicast, Unknown Unicast)</p> <p>Bandwidth control per port</p> <p>SWRR, DWRR for Scheduling</p> <p>Flow Redirect</p> <p>Precedence</p> <p>TOS</p> <p>Rate Limiting(Ingress/Egress)</p> <p>Stri Priority</p>
Security Features	<p>Port Security</p>



	<p>MAC address filter</p> <p>ARP Association (Manual, ARP scanning, DHCP snooping)</p> <p>ARP Protection</p> <p>AAA</p> <p>DAI</p> <p>DoS (Denial of Service)</p> <p>Classification of packages based on: End.MAC, IP End, TCP / UDP Ports,</p> <p>Protocol Type;</p> <p>802.1x Authentication (port-based e MAC-based)</p> <p>TACACS/TACACS+ Authentication</p> <p>RADIUS Authentication</p> <p>DHCP Filter</p> <p>Guest VLAN</p> <p>SSLv2/SSLv3/TLSv1</p> <p>SSHv1/SSHv2</p> <p>Restriction of WEB access based on: IP Address, And. MAC and Port;</p> <p>Port Isolation</p> <p>Loopback detection</p>
Management	<p>SNMP v1/v2c/v3 with Full Private MIBs</p> <p>RMON 4 groups</p> <p>WEB (HTTP/HTTPS)</p> <p>CLI (Telnet, Console, SSHv1/v2)</p> <p>Firmware upgrade via console/web/TFTP</p> <p>Configuration backup/reload</p>



	Dual firmware LLDP Configuration export/import CDP Aware OAM (IEEE802.3ah) CFM (IEEE802.1ag) sFlow Telnet client
Synchronisation, IEEE1588	Support IEEE1588v2 transparent clock
Other Features	DNS Client DHCP Relay DHCP Client DHCP Snooping DHCP Option 66 DHCP option 67 DHCP option 82 NTP/SNTP client UPNP UDLD
PoE management	Total PoE power budget control Per port PoE function enable/disable PoE admin-mode control PoE port power feeding priority Per PoE port power limitation PD classification detection



	PD alive check PoE schedule Soft-reboot PoE non-stop
Maintenance	Cable Diagnostics Ping SFP DDM (Digital Diagnostics Monitoring) Thermal protection System log (Local and Remote) Memory and CPU Monitoring Tracert/ Tracert 6

Layer 3 functions

Static Routing	IPv4 Unicast: Static Routing (Software Base) IPv6 Unicast: Static Routing (Software Base)
IPV6	IPv6 neighbour discovery (ND) Path maximum transmission unit (MTU) discovery Internet Control Message Protocol (ICMP) version 6 TCPv6/UDPv6 Ping6 Telnet(v6) Http/Https Interface IPV6 ACL IPV6

Attributs

Attribut	Valeur
----------	--------



No. d'article: 223959
Numéro de fabricant: ALL-SGI8106PMJ

Anzahl Ports PoE/LAN:	4/0
Belüftung Switch:	Lüfterlos
Einsatzort Switch:	Industrial DIN
Extra Features:	JSON-PoE-API;
LAN Geschwindigkeit:	1Gbit/s
Management:	full managed
PoE Budget:	<200 Watt
PoE Port Leistung:	30W at
SFP Geschwindigkeit:	SFP 1GBit
Poids:	0.8 Kg
Garantie:	24.00 Mois

[Cliquez ici pour découvrir d'autres articles de cette catégorie dans notre boutique.](#)