Part No.: 158925 Vendor Part No.: S21-LED-F00184

Synergy 21 LED Flex Strip 70 WW DC24V 240W IP65 **ULS 50m**





kwh/1000h:	52,80
Lumens:	3900
Watt:	48,0
Nominal Service Life:	35000 Std.
Switching Cycles:	50000
Opt. Ambient	25 °C
Temperature.:	



Synergy 21 LED Flex Strip ULS Series ULS=Ultra Long Strip

Voltage: 24V, Watt: 240W CRI>80

Light colour: warm white, 2700K

Brightness: 3900lm Beam angle: 120° Protection class: IP65 Number of LEDs: 70/m Dimensions: 50000*10*3 mm

PCB colour: white, open cable end (360±5mm) Operating temperature: -25°C to +40°C

Weight: 0.500kg

Can be shortened every 7 LED 10cm Adhesive tape: yes 3M on the back

Energy efficiency class: A

kWh/1000h: 52.8

Strip can be shortened at the cut marks with sharp scissors. !Attention! Strip must first be checked for functionality. Only split the strip when no current is present.



Part No.: 158925 Vendor Part No.: S21-LED-F00184

Our 3M adhesive tape adheres well, but should only be used as a mounting aid.

There are a variety of mounting options, such as clips, permanently elastic mounting adhesive, cable ties, etc.

Please note that LED strips must also be cooled.

Make sure that the LED strip does not exceed a working temperature of 40°C, otherwise its service life cannot be guaranteed.

No guarantee can be given for overheated LED strips

Attributes

Attribute	Value
Abstrahlwinkel:	120
Ampere:	10
CC oder CV:	CV
CRI:	>80
Dimmbar:	abhängig vom Netzteil
LED Strip Klebeband:	ja
LED Strip Breite:	10
LED Strip Höhe:	3
LED Strip kürzbar:	100
LED Strip Länge:	50000
Lichtfabe in Kelvin:	2700
Lichtfarbe:	warmweiß
Lichtfarbe in Kelvin:	2700
Lichtfarbe Name:	warmweiß
Lumen:	3900
Schutzklasse:	IP65
Volt:	24
Weight:	0.5 Kg
Warranty:	60.00 Months

Additional Images


SYNERGY 21

Part No.: 158925 Vendor Part No.: S21-LED-F00184











SYNERGY 21

Part No.: 158925 Vendor Part No.: S21-LED-F00184

Accessories

Part No.	Name
140930	Mean Well power supply - 48V 240W dimmable IP65