



Synergy 21 LED Flex Strip 700 SWW DC24V 120W IP20 CRI>90 2110



kwh/1000h:	132,00
Lumens:	10440
Watt:	120,0
Nominal Service Life:	35000 Std.
Switching Cycles:	50000
Opt. Ambient Temperature.:	25 °C



Synergy 21 LED Flex Strip 2110 super ww
2110=LED chip size 2.1mm x 1.0mm

Length: 5m
Voltage: 24V,
Watt: 24/m, 120W
Light colour: super warm white, 2700K, CRI>90 (R9>60)
Brightness: 2088lm/m , Total: 10440lm
Beam angle: 120°
Protection class: IP20
Number of LEDs: 700*2110SMD/m, total: 3500LEDs
Dimensions: 5000*12*1.4 mm
PCB colour: white,
Operating temperature: -25°C to +40°C
Shortenable every 7 LEDs 1cm
Adhesive tape: yes 3M on the back

Energy efficiency class: A+
kWh/1000h: 132

Strip can be shortened at the cut marks with sharp scissors.
!Attention! Strip must be checked for functionality beforehand.
Only split the strip when no current is present.

Our 3M adhesive tape adheres well, but should only be used as a mounting aid.

There are a variety of mounting options, such as clips, permanently elastic mounting adhesive, cable ties, etc.

Please note that LED strips must also be cooled.


Make sure that the LED strip does not exceed a working temperature of 40°C, otherwise its service life cannot be guaranteed.

No guarantee can be given for overheated LED strips.

Attributes

Attribute	Value
Abstrahlwinkel:	120
Ampere:	5
CC oder CV:	CV
CRI:	>90
Dimmbar:	abhängig vom Netzteil
LED Strip Klebeband:	ja
LED Strip Breite:	12
LED Strip Höhe:	1.40
LED Strip Klebeband:	ja
LED Strip kürzbar:	10
LED Strip Länge:	5000
Lichtfabe in Kelvin:	2700
Lichtfarbe:	warmweiß
Lichtfarbe in Kelvin:	2700
Lichtfarbe Name:	warmweiß
Lumen:	10440
Schutzklasse:	IP20
Volt:	24
Weight:	0.3 Kg
Warranty:	24.00 Months

Additional Images



Accessories

Part No.	Name
93682	Mean Well Power Supply - 24V 150W Dimmable IP65