

ALLNET MSR IO ALL4427 / 4 port 250V/10A relay in housing 'OUTPUT'

>>> [Go to the shop article](#)



EAN CODE



Highlights:

- Compatible with ALL34xx/3500/4500/5000
- 4-port relay output in metal desktop/wall-mounted housing
- switches 4 relays with ON contacts 250V/10A
- **(no longer compatible with ALL3000/ALL4000)**

The **ALL4427** is a powerful **4-port relay output** in a robust aluminium housing that is ideal for controlling various electrical loads, whether for controlling lights, pumps or other devices with a maximum current requirement of up to **10 amps** per relay. With a voltage of up to **250V** per switching contact, the ALL4427 offers reliable performance for demanding applications.

Compatibility and versatility:

- **Compatible with models** of the **ALL34xx/3500/4500/5000 series**, but no longer with ALL3000 or ALL4000.
- The connection is made via **2x RJ45 sockets**, allowing the device to be easily integrated into existing networks.

Handling and mounting:

- The aluminium housing is durable and resistant, ideal for harsh environments and use in demanding projects.
- The integrated **wall mounting bracket** enables simple and stable mounting on walls or in the control cabinet.

Multiplexing for extended applications:

- Multiple multiplexing allows several modules to be operated simultaneously on one line, which enables flexible expansion of the relay control for more extensive setups.

This 4-port relay module offers a reliable solution for controlling electrical devices and is an ideal choice for users looking for flexible application options and easy installation.

Technical details:

Element	Specification
Sensor type	4-fold relay with ON contacts 250V/10A
Chip	PCF8574
Connection:	2x RJ45 (I2C bus)
Multiplexing:	Adjustment wheel for ID
LED indicators:	1x PWR, 1x BUS, 4x contact output
How to use:	Metal walking
Environment:	Temperature operation: -45 ~ 90 °C Humidity operating: 10% ~ 85% (non-condensing) Temperature storage: -20 ~ 60 °C Humidity storage: 5% ~ 90% (non-condensing)
Labelling:	CE, RoHS
Dimensions:	79 x 50 x 24 mm (length x width x height)
Weight:	230 grams (without packaging and accessories)
Packaging contents:	1x ALL4427 4-fold relay 1x 1m connection cable

Accessories

Part No.	Name
134571	ALLNET ALL3419 / IP Building-Autom. 3x I2C, 1x USB, LAN/WLAN
98686	ALLNET ALL3500 / IP Homeautomation Appliance, 4x Sensor-Port
104126	ALLNET ALL3505 / IP Homeautomation Appliance DIN-Rail 8x I2C
206211	ALLNET MSR Central "ALL5000v2" incl. 16 Sensor Ports & 19" for IP Building Automation

[Click here to discover more items from this category in our](#)



Part No.: 98825
Vendor Part No.: ALL4427

[shop.](#)