



NOTE:

1. Test:
 - (1).100% Practical application test
 2. Storage temperature : -40℃~+70℃ - Indoors
 3. Operation temperature: -10℃~+60℃ - Indoors
 4. RoHS 3.0 and REACH Compliant
 5. PACKING:1PC/ PE bag+inner box

Accessory:
 M2.5 screws allows easy installation*2pcs
 Magnetic strip with glue length:400mm *1pcs
 Euro mains charger cable length:1.5M *1pcs

Rated wattage:4W
 Rated lamp efficacy: 81 lm/W
 Maximum Current:0.33A
 Rated voltage:12V DC
 Central lumen:324 lm
 Color Temp:6500K
 Angle:104°
 Lifespan:25000H
 Switch-on or start-up time until 60 % of full luminous flux has been reached: <1S
 Ingress Protection Grade:IP20
 IR Sensor function:

- (1) Insert an IR sensor switch in the middle of light
- (2) The detection distance is about 4-5cm.
- (3) It is installed near to 10mm of the edge of door.

Euro mains charger:
 input:100-240V-50/60Hz 0.25A
 output:DC 12V 1000mA 12W

MATERIAL LIST:

④	IR sensor switch	Touch Mode and Door Mode	1PC	
③	Light Source	High brightness 2835SMD 6500K LED	18PCS	
②	lamp chimney	PMMA transparent	1PC	
①	Housing	Aluminum alloy Silver	1PC	

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK
		Modify the length of the magnetic strip from 258mm to 400mm	2023/10/27	A1
		Modify the lamp chimney PMMA White to transparent	2023-09-26	A
		NEW		
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

<h1>SYNERGY21</h1>					
CUSTOMER		ITEM NO.	ALL-S0002256		
PRODUCT NAME	LED Cabinet lighting	manufacture country:	CHINA	UNIT	MM
DRAWNBY	CHECKBY	APPOBY	DATE		
SYNERGY21	SYNERGY21	SYNERGY21	2022-02-14		