



**DIRECTIONAL  
TWEETER**

**ANGLED TWEETER  
BRIDGE HANDLE**

**3" MIDRANGE**

**7" ANGLED DRIVER**

**TRUGRIP™**  
PATENTED WITH SWARM TECHNOLOGY

**New Toolless Design**  
TruGrip technology, a 2-step mechanical dogear, ensures the tightest grip with zero sag.



**QUICK  
CONNECT**

**Quick. Easy. Secure.**  
The fastest way to terminate a speaker. Connect speaker wire to rough-in ring during pre-wire, then use the Quick Connect cable to tether to the speaker's Quick Connect.



## REVOLVE™ SERIES

TruAudio's Revolve Series speakers are the answer to any home theater installation project. These Speakers feature our patented TruGrip technology and are QuickConnect ready. The series has been updated with a more functional angled 7" woofer, in both a Polypropylene (REV72) and Carbon Fiber (REV71) finish. Providing you a wide array of price and performance options. Both models feature a 3-way design - a pivoting tweeter and mid-range (LCR models only). The depth of the reveal into the living space has been decreased by 40% allowing the speakers to virtually disappear into the ceiling. TruAudio's Revolve Series also features the revolutionary and patented TruGrip™ technology which incorporates a 2-step, toolless mechanical dogear, significantly reducing the time spent on trim-outs. TruAudio's QuickConnect™ adapters were also incorporated, shaving even more time off of trim-outs (if QuickConnect™ pre-construction brackets were used in the rough-in stage). All speaker models conveniently fit into one Rough-In Ring, the RC-879. The REV71 and REV72 speaker models are available in LCR or Surround models. Finally, all updated REV Speakers now include a vented protective backbox to protect all critical components on the back of the speaker, and it includes a tweeter bridge that doubles as a built-in handle!



### REV71

Speaker Type: In-ceiling angled, 3-way  
 Woofer: 7" woven carbon fiber  
 Midrange: 3" carbon fiber, swivel  
 Tweeter: 1" titanium, swivel  
 Power: 175 watts  
 Impedance: 8  $\Omega$   
 Freq Response: 36 - 20k Hz (+/-3 dB)  
 Sensitivity: 92 dB  
 Grill Type: Microperf, frameless  
 Rough-in Ring: RC-879  
 Finish Dims: 10.5" (267 mm) diameter  
 6.0" (152 mm) deep  
 Cutout Dims: 9.9" (251 mm) diameter



### REV71SUR

In-ceiling angled, surround  
 7" woven carbon fiber  
 ---  
 (2) 1" titanium, swivel  
 175 watts  
 8  $\Omega$   
 36 - 20k Hz (+/-3 dB)  
 92 dB  
 Microperf, frameless  
 RC-879  
 10.5" (267 mm) diameter  
 6.0" (152 mm) deep  
 9.9" (251 mm) diameter



### REV72

Speaker Type: In-ceiling angled, 3-way  
 Woofer: 7" polypropylene  
 Midrange: 3" polypropylene, swivel  
 Tweeter: 1" silk dome, swivel  
 Power: 150 watts  
 Impedance: 8  $\Omega$   
 Freq Response: 38 - 20k Hz (+/-3 dB)  
 Sensitivity: 91 dB  
 Grill Type: Microperf, frameless  
 Rough-in Ring: RC-879  
 Finish Dims: 10.5" (267 mm) diameter  
 6.0" (152 mm) deep  
 Cutout Dims: 9.9" (251 mm) diameter



### REV72SUR

In-ceiling angled, surround  
 7" polypropylene  
 ---  
 (2) 1" silk dome, swivel  
 150 watts  
 8  $\Omega$   
 38 - 20k Hz (+/-3 dB)  
 91 dB  
 Microperf, frameless  
 RC-879  
 10.5" (267 mm) diameter  
 6.0" (152 mm) deep  
 9.9" (251 mm) diameter