

# EtherHaul™ 600/614 Series



## Street-level gigabit V-band radios

### Typical Applications

- Safe/Smart City Networks
- Business Broadband
- Wi-Fi Hotspot Backhaul
- Gigabit to the Home (GTTH)
- Small Cell Backhaul

### Gigabit Throughput on Every Street

The EtherHaul™-600 series delivers up to 1Gbps in a form factor that is small enough and rugged enough to be deployed at street level on poles and light fixtures. With the EH-614, Siklu offers a model that can tune in the lower and upper portions of the 60GHz V-Band, covering 11GHz of spectrum in a single product. When operating in the upper 60GHz portion of the band, distances can be achieved that are as much as 50% further than operation in the lower bands due to the absence of oxygen absorption.

### Interference-Free Operation and Scalable Deployments

The unlicensed 60GHz V-band spectrum avoids interference typically seen in unlicensed bands through a combination of means. With 7 to 9GHz allocated around the world and 14GHz in the US and the UK, there is ample spectrum for mass, dense deployments. The V-band is also characterized by pencil-thin beams, meaning a small amount of spatial separation is often enough isolation, allowing aggressive frequency reuse schemas of the 14 full-capacity non-overlapping channels.

### Robust Carrier Class Construction

The all-weather IP-67 sealed radio guarantees carrier-grade performance under even the harshest weather conditions. Designed to operate in temperatures from -45°C to +55°C this product has been deployed around the world from Siberia to Texas. Carrier class specifications are backed up by an MTBF measured in decades not years.

### Streamline Operations with Carrier Ethernet & Synchronization

The EH-600/614 both have MEF-compliant integrated Carrier Ethernet switches. This helps streamline operations with configurable service-aware QoS, bandwidth management and OAM. For mobile operators, optional built-in timing synchronization with Sync-E and 1588v2 ensures smooth performance over packet based backhaul networks. With a built in switch, customers avoid additional boxes, power supplies etc and can leverage not only the layer 2 features but can be powered from a PoE out port on the radio.

### Easiest Installation & Management

Virtually any installer can deploy the EH-600/614 with very little training or experience. Physical installation from opening the box to passing traffic can be as little as 15 mins when using pre-configurations loaded into the radio. Once deployed advanced configuration is available via an intuitive web GUI, while additional services may be remotely activated from a NOC. An IPERF integrated TCP and UDP load tester, and a spectrum analyzer streamline the commissioning and the troubleshooting.

### Exceptional Value

With minimal deployment costs and virtually no maintenance, the EH-600 series minimizes Total Cost of Ownership (TCO) and provides a Return On Investment (ROI) often measured in months, providing an unbeatable price/Mb. The EH-614 wide frequency support reduces TCO with less inventory while benefiting from extended range achievable with the upper 60GHz spectrum.

### Field Proven Technology

EtherHaul™ is the world's bestselling millimeter wave radio. Tens of thousands of units have been deployed and are performing reliably in stringent weather conditions all over the globe. The EH-600/614 incorporates Siklu's integrated all-silicon technology, which increases reliability while reducing size and cost. The result is a small form factor radio with a proven 90-year MTBF and an unbeatable price/throughput.



# EtherHaul™ 600/614 Series Specifications



		EH-614TX	EH-600TX	EH-600T
Frequency & Duplexing	57-66GHz, TDD		✓	✓
	57-68GHz, TDD	✓		
Channels	125/250/500MHz wide, 11 non-overlapping channels		✓	✓
	125/250/500MHz wide, 14 non-overlapping channels	✓		
Modulation & Adaptive rate	5 levels of hitless adaptive bandwidth, coding and modulation - Link budget boost up to 25dB	Up to QAM 64	Up to QAM 64	Up to QAM 64
Throughput [Mbps]	Aggregated throughput up to (with upgrade of capacity via license)	1000	1000	1000
Link budget (BER=10 <sup>-6</sup> )	Including integrated 36dBi antenna gain	162dB	162dB	162dB
Interfaces	3xGbE copper ports	✓	✓	✓
Ethernet features	IEEE 802.1d transparent bridging VLAN & VLAN stacking, 4K VLANs. Jumbo Frames: 16KB. MEF 9, 14 and 21 compliant Ethernet services. Ring Protection Switching: ITU-T G.8031 ERPS (*FTL). Link state propagation. Configurable QOS aware forwarding. 8 level H-QOS with flexible mapping options: L2 (802.1p, VLAN id), L2.5 (MPLS EXP) and L3 (DSCP).	✓	✓	✓
Timing	Synchronous Ethernet and 1588v2 TC (*FTL)	-	-	✓
Encryption	AES 128-bit and 256-bit (*FTL)	✓	✓	✓
Management & provisioning	Zero-touch turn up; In-band, out-of-band management. Web GUI (one-click configuration of local and remote units) & Embedded CLI. SNMPv2/3, TACACS+, RADIUS. Link OAM & Connectivity Fault Management (CFM): IEEE802.3ah & IEEE802.1ag; performance monitoring: ITU-T Y.1731 (*FTL). IPERF TCP/UDP capacity tester.	✓	✓	✓
Topologies	Ring, daisy-chain, mesh	✓	✓	✓
Conformance	Radio: FCC Part 15.255, ETSI EN 302 217-3 & UK IR 2078 & IR 2000; EMC: USA FCC 47CFR.part 15 & ETSI EN 301 489; Safety: UL/EN 60950	✓	✓	✓
Power supply	PoE+ (IEEE 802.3at), 26W without PoE-Out; up to 78W with PoE-Out	✓	✓	✓
PoE-Out	Port 2 and Port 3 (IEEE 802.3at): 26W+26W / 13W+40W / 50W+0W (*FTL).	✓	✓	✓
Environmental	Operating Temperature: -45° to +55°C (-49° to +131°F) Ingress Protection Rating: IP67	✓	✓	✓
Dimensions	ODU + 0.5ft antenna: 5.9" x 6.1" x 3.5" (16.5 x 16.5 x 10cm)	✓	✓	✓
Weight	ODU + 0.5ft antenna: 3.9 lbs. (1.8 kg)	✓	✓	✓

\*FTL note: requires feature license.