

## Finder installation contactor 25A (inrush current limiter)



Installation contactor for 35 mm rail, 2  
NO contact for 25 A / 250 V AC,  
Contact material: AgSnO<sub>2</sub>, max.  
switching capacities at 230 V AC: AC1 6250  
VA, AC15 1800 VA, 1-phase motor load, AC3  
(230 V AC) 1 kW, rated current AC AC-  
7c 10 A, incandescent and halogen lamps 2000 W,  
Compact fluorescent lamp (energy-saving lamp)  
200 W, fluorescent lamp with electronic ballast 800 W,  
Fluorescent lamp with CCG 500 W, LED (230  
V AC) 200 W, LV halogen lamps or LED  
with ECG 200 W, LV halogen lamps or  
LED with CCG 800 W. Coil: 230 V AC/DC,  
width 17.5 mm, with auto-off-on switch,  
LED and mechanical  
switch position indicator, protection class: IP 20

## Accessories

Part No.	Name
148726	Synergy 21 - Waterproof connector 1:1

Part No.	Name
148727	Synergy 21 - Waterproof connector 1:2
148730	Synergy 21 - Waterproof connector box 3 ports
148729	Synergy 21 - Waterproof connector box 3 ports transparent
148728	Synergy 21 - Waterproof connector box 4 ports