



## NOTE:

## 1. Electrical test:

- (1). 100% open short & miss wire test;
- (2). Insulation resistance: DC 300V 0.01s 10M ohm min;
- (3). Contact resistance: 3 ohm max;

## 2. Computer + Monitor test

- (1). Resolution: 3840\*2160@120Hz

## 3. Marking: DisplayPort Cable E\*\*\*\*\* 兄 AWM STYLE 20276 80°C 30V VW-1

## 4. RoHS (EU2015/863) and REACH Compliant

## 5. PACKING: 1PC/PE BAG+label

## MATERIAL LIST:

⑥	SHIELDING	IRON SHELL SHIELDING	2	
⑤	DUST CAP	LD PE	2	
④	TUBE END	BLACK PVC 45P	2	
③	OUTER COVER	BLACK ABS ASSEMBLY TYPE	2	
②	CONNECTOR	DP 20P/M WITH LATCHING BLACK INSULATION, THE PIN GOLD PLATED, THE SHELL FOR GOLD PLATED	2	
①	CABEL	DP1.4V CABLE[(30AWG TC)*1P+(30AWG TC)+FAM]*5+(30AWG TC)*4C+AL-FOIL+(30AWG TC)+BRAID, JACKET:PVC black OD:6.0±0.2mm	1	

SYNERGY21

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK	CUSTOMER	ITEM NO.	S215440V4			
					PRODUCT NAME	30AWG DisplayPort 1.4V Male-Male Black Cable Gold plating	manufacture country:	CHINA	UNIT	MM
		NEW	2019-09-06	A	DRAWNBY	CHECKBY	APPOBY	DATE		
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.	SYNERGY21	SYNERGY21	SYNERGY21	2019-09-06		