## **VS481**A



# **4-Port HDMI Switch**

Expand Your Home Theater System!


The VS481A 4-Port HDMI Switch allows you to quickly and easily connect 4 HDMI input sources to your HDMI display device. The VS481A allows convenient switching between digital devices such as DVD players, satellite receivers and digital camcorders. You can select the desired input source via a remote control unit or pushbuttons located on the front of the switch.





#### Features \_

- Allows up to four HDMI A/V sources to be connected to one HDMI display
- Toggle between A/V sources using remote control or front panel pushbuttons
- Supports high-resolution video HDTV resolutions of 480p, 720p, 1080i, 1080p (1920x1080); VGA, SVGA, SXGA, UXGA (1600x1200) and
- WUXGA (1920x1200)
- Supports 12-bit Deep Color for HDMI formats Supports Dolby True HD and DTS HD Master Audio
- Up to 60 Hz refresh rate
- Long distance transmission up to 20 m (24 AWG) and 15 m (28 AWG)
- Built-in bi-directional RS-232 serial remote port for high-end system control • Plug-and-play - no software installation required
- DDC Compatible
- HDMI 1.3b compliant
- HDCP 1.1 compliant
- Supports HDMI Type A 19-pin female connector
- Signaling rates up to 2.25 Gbits in support of 1080p display
- All-metal casing
- · LED indication of video source devices
- · Easy and affordable way to add four HDMI inputs to your home theater system



### Specifications .....

Function			VS481A
Display Connections			1
Connectors	Device	HDMI In	4 x HDMI Type A Female (Black)
	Display	HDMI Out	1 x HDMI Type A Female (Black)
	RS-232 Port		1 x DB-9 Female (Black)
	Power		1 x DC Jack
LEDs	On Line		4 (Orange)
	Selected		4 (Green)
Video			HDTV resolutions of 480p, 720p, 1080i, 1080p (1920x1080); VGA, SVGA, SXGA, UXGA (1600x1200) , WUXGA (1920x1200)
Power Consumption			DC5.3V, 2.4W
Environment	Operating Temp.		0–50°C
	Storage Temp.		-20–60°C
	Humidity		0–80% RH, Non-condensing
Physical Properties	Housing		Metal
	Weight		0.47 kg
	Dimensions (L x W x H)		20.00 X 8.00 X 2.50 cm

\* The specifications and pictures are subject to change without notice



### **Headquarters**

ATEN International Co., Ltd. 3F, No.125, Sec. 2, Datung Rd. Sijhih City, Taipei 221, Taiwan Tel: 886-2-8692-6789 Fax: 886-2-8692-6767 E-mail : E-mail : online@aten.com.tw

#### Setup -----