

AXIS Camera Station S1216 Tower

Out-of-the-box ready recording servers

Featuring powerful components, this secure, scalable recording server offers high performance and support for powerful applications and features. For quick and easy installation, AXIS S1216 Tower is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. And, a Trusted Platform Module (FIPS 140–2 level 2 certified) ensures secure storage of all cryptographic keys and certificates. Plus, all supported products are available in one price list for a one-stop-shop experience. Furthermore, it offers services such as Keep Your Hard Drive, Next Business Day Onsite Support, and a 5-year warranty

- > Scalable and powerful solution
- > Flexible storage options including RAID
- > 8 TB storage included
- > 16 AXIS Camera Station licenses included
- > Extensive support and 5-year warranty



AXIS Camera Station S1216 Tower 16 AXIS Camera Station core licenses included and tied to Licenses the hardware. Can be upgraded with additional licenses (sold Supports the same split scenarios as for live view on one monitor. separately). Cybersecurity System Qualified for 64 doors and 32 video channels with a total Documentation AXIS Hardening Guide recording bitrate up to 256 Mbit/s which corresponds to 4 MP. scalability AXIS Vulnerability Management Policy 30FPS per channel in a retail scenario. AXIS Security Development Model Check AXIS Site Designer for storage estimates. To download documents, go to axis.com/support/product-security Tested with: To read more about Axis cybersecurity support, go to 6 live view clients axis.com/cvbersecurity 2 clients performing heavy playback or scrubbing operations General Hardware Operating system Microsoft® Windows® 10 IoT Enterprise LTSC 2021 Processor Intel® Core[™] processor Built-in operating system recovery: yes 16 GB (2 X 8 GB) Memory Operating system drive: 256 GB SSD Cold swappable Enterprise Class SATA HDD, 7200 rpm. Support for encrypted operating system drive and recording drive Storage Security Total HDD slots: 2 FIPS 140-2 level 2 certified Trusted Platform Module (TPM 2.0) Free HDD slot: 1 0 °C to 45 °C (32 °F to 113 °F) Operating Out-of-the-box storage: 8 TB (1x 8 TB) conditions Humidity 20-80% RH (non-condensing) RAID Factory RAID level: No RAID Storage -40 °C to 65 °C (-40 °F to 149 °F) Supported RAID levels: 0, 1 conditions Humidity 5-95% RH (non-condensing) Graphics card Intel® UHD graphics Approvals Power 500 W 80+ Platinum EN 55032 Class B, EN 55035, EN 61000-3-2, EN 61000-3-3, (100-240 V AC, 7.0 A, 50/60 Hz) FCC Part 15 Subpart B Class B, ISED ICES-003 Class B, RCM AS/NZS CISPR 32 Class B, KS C 9832 Class B, KS C 9835, Connectors Front side: VCCI 32-1 Class B. BSMI 1x Universal audio jack Safety 2x USB 2.0 IEC/EN/UL 62368-1, EN 62311, NOM-019-SCFI-1998 1x USB 3.2 1x USB 3.2 gen 2 2x2 USB-C port Compliance NDAA (National Defense Authorization Act) Rear side: TAA (Trade Agreements Act) 1x Universal audio jack Dimensions 367 x 169 x 301 mm (14,5 x 6.7 x 11.8 in) 3x DisplayPort[™] 1.4a 1x Header for remote power button Weight 6.6 kg (13.2 lb) 4x USB 3.2 Wall plug power cord Included 2x IISR 20 accessories 1x RJ45 Ethernet Optional Axis joysticks and control boards Video accessories Enterprise hard drives Video streaming Live view: For more accessories, see axis.com 1 stream x 4K at 30 fps Next Business Day Onsite Support Services 4 split x 1080p at 30 fps Keep Your Hard Drive 9 split x 720p at 30 fps 16 split x 360p at 15 fps Warranty 5-year warranty, see axis.com/warranty 25 split x 360p at 15 fps 36 split x 360p at 15 fps

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on *axis.com*

Any combination of the above for maximum two 4K monitors where only one monitor can show streams at 30 fps.

Environmental responsibility: axis.com/environmental-responsibility www.cxis.com T10185189/EN/M1.5/2212



