
Part No.: 158703 Vendor Part No.: SYS-RL1

# Synergy 21 LED subordinate wall washer 24W RGB+CCT IP66 24V \*Milight/Miboxer\*





kwh/1000h:	26,40
Lumens:	1800
Watt:	24,0
Nominal Service Life:	35000 Std.
Switching Cycles:	50000
Opt. Ambient Temperature.:	25 °C



Experience the impressive performance of the RGB+CCT LED Wall Washer Light, a high-quality lighting product designed for versatile applications. With an output of 24W and an input voltage of DC24V, this wall washer light delivers exceptional brightness and flexibility in lighting.

The colour temperature is adjustable from 2700K to 6500K, allowing you to adjust the light colour as required and create the perfect atmosphere. With a luminous flux of 1800LM and a luminous efficacy of 75LM/W, this product provides efficient lighting that is also effective in large areas.

Thanks to the **high colour rendering index (CRI >80)**, the objects in your surroundings are illuminated naturally and vividly. The **lifespan of 50,000 hours** guarantees long-term use without frequent replacement.

The RGB+CCT LED Wall Washer Light impresses with its beam angle of 15° x 60°, which enables a wide and uniform light distribution, and an illumination distance of over 15m, ideal for illuminating larger areas. With protection class IP66, this light is ideally suited for outdoor use and provides reliable protection against dust and water.

Made from **die-cast aluminium and stalinite**, it offers a robust and durable construction. The Wall Washer Light is an excellent choice for decorative and functional lighting solutions in a variety of environments.

Optimise your lighting with the **RGB+CCT LED Wall Washer Light** and enjoy a powerful and customisable lighting solution to suit your needs.

Product Name: RGB+CCT LED Wall Washer Light

(Subordinate Lamp)
Model No.: SYS-RL1

Part No.: 158703 Vendor Part No.: SYS-RL1

Input Voltage: DC24V

Power: 24W

Working Temperature: -20~60° Colour temperature: 2700~6500K

Luminous Flux: 1800LM Light Efficiency: 75LM/W

CRI: >80

Lifespan: 50000h Beam Angle: 15\*60° Illumination distance: >15m

IP Rate: IP66

Housing Material: Die-cast aluminium, stalinite

Energy efficiency class: A+

kWh/1000h: 26.4

#### **Attributes**

Attribute	Value	
Abstrahlwinkel:	15*60	
Ampere:	1	
CC oder CV:	CV	
Dimmbar:	Ja	
Grösse:	1017*64*62	
LED - Gehäusematerial:	Aluminium	
Lichtfarbe:	RGB-WW	
Lichtfarbe in Kelvin:	2700~6500	
Lumen:	1800	
Schutzklasse:	IP66	
Volt:	24	
Weight:	1.9 Kg	
Warranty:	24.00 Months	

#### **Additional Images**

Part No.: 158703 Vendor Part No.: SYS-RL1









Part No.: 158703 Vendor Part No.: SYS-RL1

#### Application















Part No.: 158703 Vendor Part No.: SYS-RL1

#### **Accessories**

Part No.	Name
158705	Synergy 21 LED subordinate controller 1-channel host *Milight/Miboxer*
158704	Synergy 21 LED subordinate controller 1-channel amplifier *Milight/Miboxer*
158699	Synergy 21 LED subordinate garden lamp 15W RGB+CCT with RF and WLAN IP65 24V Milight/Miboxer*
158700	Synergy 21 LED subordinate garden lampe 9W RGB+CCT with RF and WLAN IP65 24V *Milight/Miboxer*
158702	Synergy 21 LED subordinate pool light 12W RGB+CCT with RF and WLAN *Milight/Miboxer*
158703	Synergy 21 LED subordinate wall washer 24W RGB+CCT IP66 24V *Milight/Miboxer*
158962	Synergy 21 LED subordinate kabel/plug SYS series *Milight/Miboxer*
158963	Synergy 21 LED subordinate kabel/plug SYS series *Milight/Miboxer*
158964	Synergy 21 LED subordinate kabel/plug SYS series *Milight/Miboxer*
158965	Synergy 21 LED subordinate kabel/plug SYS series *Milight/Miboxer*