



NOTE:

- Electrical test:
 - 100% open short & miss wire test;
 - Insulation resistance:DC 300V 0.1S 10MΩ;
 - Conductor resistance:2Ω Max;
 - SSD TEST:1800MB/S (min)
- Feature:
 - Full-featured USB4 Type-C Cable (USB4 Gen3x2)
 - Transmission rate Up to 40Gbps
 - Resolution up to single 8k@60Hz or dual 4k@60Hz
 - Backwards compatible with USB 3.1, 3.0 and 2.0 and Thunderbolt 3
 - Supports USB power delivery 3.1 (EPR 20V/5A-48V/5A) 240W
- RoHS 2.0 and REACH Compliant
- Packing:IPC/SYNERGY 21 bag+label

ITEM NO.	LENGTH (mm)
	500±20
	1000±20
	1200±30
S215316	1500±30
S215317	2000±30

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT' Y	REMARK
⑤	MOULDING	PVC Black	2	
④	E-mark	USB4 GEN3*2 40Gbps 240W/5A	2	
③	Housing	Aluminum housing Gray beveled highlighting	2	
②	USB TYPE C	USB 4 C/M Solder Type,Black PBT Insulation,The Pin Gold Plating, the shell for Nickel Plating With E-MARK	2	
①	CABLE	USB4 GEN3*2 CABLE[32AWG BC*1P+D+AM+HM]*4C+32AWG BC*1P+32AWG BC*4C+24AWG BC*2C+D+AM+B] PVC+Cotton braid Jacket BLACK OD:4.8±0.15MM	1	

					SYNERGY 21						
					CUSTOMER		ITEM NO.		SEE THE CHART		
					PRODUCT NAME		manufacture country:		CHINA	UNIT	MM
					NEW		2024-07-22		AO		
BY	CHK	REVISION RECORD MODIFICATIONS			DATE	REV.	DRAWNBY	CHECKBY	APPOBY	DATE	
							SYNERGY 21	SYNERGY 21	SYNERGY 21	2024-07-22	

USB4 40Gbps EPR240W USB Type C male -C male